



## NEW WR250 BALER

The NEW  
**KERRUSH 250**  
Model is available  
in both **AIR** or  
**HYDRAULIC**  
versions.



### FEATURES

**Front Tying System**

**New Baler Base**

**Protective Spools Cover**

**New Type of Handle**

**Top Guard for the Baler**

**Slotted Holes**

### BENEFITS

- ◆ Ease of Tying
- ◆ Baler can be moved by means of Pallet Truck
- ◆ Completely Weatherproof Baler
- ◆ Tidier Looking Baler
- ◆ Eliminates Scratching of Paint
- ◆ More User-Friendly
- ◆ Top Opening for Extra Safety
- ◆ Weatherproof Baler
- ◆ Ease of Maintenance
- ◆ Smoother Feeding of Strapping



# NEW WR250 BALER

## TECHNICAL SPECIFICATION WR250 AIR AND HYDRUALIC BALER

STANDARD FEATURES	WR250A	WR250H
<b>Baling Force</b>	<b>Up to 3 T</b>	<b>Up to 4 T</b>
<b>Bale Size Indicator</b>	<b>External</b>	<b>External</b>
<b>Number of Rams</b>	<b>1</b>	<b>1</b>
<b>Technical Specification</b>		
<b>Motor Type</b>	<b>220 S Phase</b>	<b>220 S Phase</b>
<b>Operator Control</b>	<b>AIR</b>	<b>24V Standard</b>
<b>Auto Shut Down</b>	<b>Standard</b>	<b>Standard</b>
<b>Operating Cycle</b>	<b>Manual Up/ Down</b>	<b>Manual Up/ Down + Auto</b>
<b>Emergency Stop</b>	<b>Standard</b>	<b>Standard</b>
<b>Opt Cycle time</b>	<b>35 Secs</b>	<b>30 Secs</b>
<b>Machine Dimensions</b>		
<b>Height</b>	<b>2100 mm</b>	<b>2100 mm</b>
<b>Width</b>	<b>750 mm</b>	<b>750 mm</b>
<b>Depth</b>	<b>500 mm</b>	<b>500 mm</b>
<b>Bale Dimensions</b>		
<b>Height</b>	<b>700 mm (Var)</b>	<b>700 mm (Var)</b>
<b>Width</b>	<b>600 mm</b>	<b>600 mm</b>
<b>Depth</b>	<b>400 mm</b>	<b>400 mm</b>
<b>Approx Bale Weight</b>		
<b>Weight</b>	<b>30 - 70 Kgs</b>	<b>30 - 70 Kgs</b>